

Vanguard IV Level Gauging System



Key System Elements:

- Metritape level sensors with optional temperature detectors
- Sensor housings used to mount and protect sensors and to make cable terminations
- Central conditioning unit which performs signal conditioning, processing and calibration

Features and Benefits:

- RS232 / 485 interface to control system
- Level and volume with optional temperature and inert gas pressure data
- Utilizes rugged resistance-tape sensors
- Sensors totally accessible from tank top
- Flexible resistance-tape sensors follow the contour of J-shaped ballast tanks
- One sensor technology serves cargo, ballast, service and draft

- Vanguard IV's program derives the vertical level when stillpipes are curved. It can also compensate for list and trim manually or automatically when draft sensors are included
- Sensors can be mounted in pairs to satisfy Independent High Alarm regulations with only one deck penetration

Description:

The industry trend of integrating onboard instrumentation systems requires a streamlined approach to tank gauging. JOWA USA has responded to this demand with the Vanguard Level Gauging System, a simple, low cost solution that delivers high performance.

The Vanguard System provides the critical link between JOWA USA's reliable resistance-tape level sensors and the centralized control system aboard any vessel type, including tankers, container vessels, gas carriers and FPSO's.

Vanguard IV Level Gauging System

Description Continued:

The Vanguard Level Gauging System sends tank level, temperature, volume, inert gas pressure and draft data via an RS232 / 485 interface to any shipboard control system. This direct serial data communication provides a cost advantage over traditional analog systems.

Vanguard delivers more accuracy than traditional ballast, fuel, and draft gauging methods, resulting in better operational control and more efficient vessel management.

Technical Data:

Channels: 120 Maximum in groups of 30, intrinsically safe or non-intrinsically safe

Operating Temperature: Electronics 0-50°C (refer to sensor data sheets for sensor temperature data)



Output: RS232/485 Modbus, other protocols available

Input Power: 115VAC $\pm 30\%$ 60HZ, 230VAC $\pm 30\%$ 60 HZ. Integral power isolation unit converts to 120VAC

Relays: 13 total; 8 level/temp/inert gas pressure, 1 system fault, 2 horn, Form C 3 Amp at 220VAC, 2 API 100mA at 50VDC

Enclosure: NEMA 12 for indoor mounting, hinged left. Cable entry from bottom of cabinet

Weight: 54kg (120 lbs.)



60 CHANNEL VANGUARD IV SHOWN WITH 2 MULTIPLEXED CONDITIONING CARDS

Disclaimer:

This is not a specification and all information is provided in good faith. Since conditions of use are beyond the control of JOWA USA, Inc., the information contained herein is without warranty, whether express, implied or otherwise. Final determination as to the suitability, merchantability or fitness of any information, material or product for a particular purpose, or any patent infringement, is the sole responsibility of the user. JOWA USA, Inc. does not assume liability for injury arising from the use of the information, material or product, and assumes no liability for any damages, whether direct, indirect, consequential, special, incidental, punitive or otherwise. For additional information regarding JOWA USA, Inc.'s limited warranty, refer to the Terms and Conditions that are currently in effect.



JOWA USA, Inc.
Littleton, MA 01460 USA
Tel: 978-486-9800 E-mail: info@jowa-usa.com
www.jowa-usa.com